


Specifications for  
 Model: GM-BS-08  
 Outdoor LED Baseball Scoreboard



SCOREBOARDS.net

Cabinet Dimensions, Weight, and Electrical Requirements

- 5 ft. x 10 ft. x 6 in.
- 0 pounds
- 120 VAC, 2 amps, 60 Hz

Display Functions and Captions

Function	Height	LEDs	Range	Caption Text	Caption Size
Guest Score:	18 in.	336	0-99	GUEST	7 in. x 30 in.
Home Score:	18 in.	336	0-99	HOME	7 in. x 27 in.
Inning:	18 in.	168	0-9	INNING	7 in. x 31 in.
Ball:	4 in.	42	3 bullets	BALL	7 in. x 23 in.
Strike:	4 in.	42	2 bullets	STRIKE	7 in. x 33 in.
Out:	4 in.	63	2 bullets	OUT	7 in. x 18 in.
Hit:	4 in.	21	1 bullet	H	7 in. x 6 in.
Error:	4 in.	21	1 bullet	E	7 in. x 6 in.

Optional Equipment

- Wireless RF communication system
- Data cable
- Carrying case for control console
- Team Name in place of HOME
- 37-key control console with LCD display

Standard Equipment

- Super-bright energy efficient LEDs (choose red or amber)
- 100% solid state microprocessor-controlled electronics
- Mounting hardware for clamping to posts
- Simplified 15-key control console
- Junction box and 10 ft. patch cable for data
- Automotive grade baked-on enamel-based paint (choose from 16 standard colors)
- Rust-free aluminum cabinet
- ETL listed to UL standard
- Five-year limited warranty
- Toll-free technical support via phone for the life of the product