Specifications for
Model: DN-1131
Outdoor LED Baseball Scoreboard

SCOREBOARDS.net

Cabinet Dimensions, Weight, and Electrical Requirements

- 6 ft. x 8 ft. x 6 in.
- 190 pounds
- 120 VAC, 2 amps, 60 Hz

Display Functions and Captions

Function	Height	LEDs	Range	Caption Text	Caption Size
Guest Score:	18 in.	336	0-99	GUEST	6 in. x 28 in.
Home Score:	18 in.	336	0-99	HOME	6 in. x 25 in.
Guest Pitches:	11 in.	200	0-99	PITCH COUNT	6 in. x 28 in.
Home Pitches:	11 in.	200	0-99	PITCH COUNT	6 in. x 28 in.
Clock:	11 in.	300	9 hours	(none)	N/A
Inning:	18 in.	168	0-9	INN	6 in. x 15 in.
Ball:	4 in.	63	3 bullets	BALL	6 in. x 21 in.
Strike:	4 in.	42	2 bullets	STRIKE	6 in. x 31 in.
Out:	4 in.	42	2 bullets	OUT	6 in. x 17 in.

Optional Equipment

- Wireless RF communication system
- Data cable
- Carrying case for control console
- Team Name in place of HOME

Standard Equipment

- Super-bright energy efficient LEDs (choose red or amber)
- 100% solid state microprocessor-controlled electronics
- Mounting hardware for clamping to posts -- no need for on-site fabrication
- 37-key control console with LCD display
- Junction box and 10 ft. patch cable for data
- Automotive grade baked-on enamel-based paint (choose from 16 standard colors)
- Rust-free aluminum cabinet
- ETL listed to UL standard
- Five-year limited warranty
- Toll-free technical support via phone for the life of the product