
Outdoor LED Baseball Scoreboard



SCOREBOARDS.net

Cabinet Dimensions, Weight, and Electrical Requirements

- 6 ft. x 20 ft. x 6 in.
- 500 pounds
- 120 VAC, 5 amps, 60 Hz

Display Functions and Captions

Function	Height	LEDs	Range	Caption Text	Caption Size
Guest Runs-By-Inning:	11 in.	1000	10 each 0-9	GUEST	8 in. x 40 in.
Home Runs-By-Inning:	11 in.	1000	10 each 0-9	HOME	8 in. x 36 in.
Guest Total Runs:	11 in.	200	0-99	RUNS	5 in. x 18 in.
Home Total Runs:	11 in.	200	0-99	RUNS	5 in. x 18 in.
Guest Total Hits:	11 in.	200	0-99	HITS	5 in. x 15 in.
Home Total Hits:	11 in.	200	0-99	HITS	5 in. x 15 in.
Guest Total Errors:	11 in.	100	0-9	ERR	5 in. x 14 in.
Home Total Errors:	11 in.	100	0-9	ERR	5 in. x 14 in.
Batter Number:	15 in.	242	0-99	BATTER	6 in. x 34 in.
Ball:	15 in.	121	blank, 1, 2, 3	BALL	6 in. x 22 in.
Strike:	15 in.	121	blank, 1, 2	STRIKE	6 in. x 33 in.
Out:	15 in.	121	blank, 1, 2	OUT	6 in. x 18 in.
Hit:	15 in.	91	"H"	H	6 in. x 6 in.
Error:	15 in.	91	"E"	E	6 in. x 6 in.
Error Fielder Position:	15 in.	121	0-9	(none)	N/A

Optional Equipment

- Wireless RF communication system
- Data cable
- Carrying case for control console

Standard Equipment

- 37-key control console with LCD display
- Junction box and 10 ft. patch cable for data
- Automotive grade baked-on enamel-based paint (choose from 16 standard colors)
- Five-year limited warranty
- Toll-free technical support via phone for the life of the product