

|  | © |
|--|---|
|--|---|

# SCOREBOARDS.net

### Cabinet Dimensions, Weight, and Electrical Requirements

- 2-1/2 ft. x 2 ft. x 6 in.
- 30 pounds each
- 120 VAC, 1 amp, 60 Hz

### **Display Functions and Captions**

| Function               | Height | LEDs | Range      | Caption Text | Caption Size |
|------------------------|--------|------|------------|--------------|--------------|
| Shot Clock:            | 12 in. | 284  | 0-99       | (none)       | N/A          |
| Clock:                 | 6 in.  | 264  | 99 minutes | (none)       | N/A          |
| Horn Visual Indicator: | 4 in.  | 42   | 2 bullets  | (none)       | N/A          |

#### **Optional Equipment**

- Wireless RF communication system
- Data cable
- Carrying case for control console
- Up to four console outputs for multiple dipalys

## Standard Equipment

- 100% solid state microprocessor-controlled electronics
- 37-key control console with LCD display
- Junction box and 10 ft. patch cable for data
- Automotive grade baked-on enamel-based paint (choose from 16 standard colors)
- Rust-free aluminum cabinet
- ETL listed to UL standard
- Five-year limited warranty
- Toll-free technical support via phone for the life of the product

800-230-0948 www.scoreboards.net DN-2180 Specifications Updated 2010-Sep-21