

SCOREBOARDS.net

Cabinet Dimensions, Weight, and Electrical Requirements

- 5 ft. x 10 ft. x 6 in.
- 170 pounds
- 120 VAC, 2 amps, 60 Hz

Display Functions and Captions

Function	Height	LEDs	Range	Caption Text	Caption Size
Clock:	18 in.	572	99 minutes	(none)	N/A
Guest Score:	15 in.	242	0-99	GUEST	9 in. x 32 in.
Home Score:	15 in.	242	0-99	HOME	9 in. x 29 in.
Period:	15 in.	121	blank, 1, 2, 3, 4	PERIOD	9 in. x 36 in.

Optional Equipment

- Wireless RF communication system
- Data cable
- Carrying case for control console
- Team Name in place of HOME
- Up to four console outputs for multiple dipalys

Standard Equipment

- Super-bright energy efficient LEDs (choose red or amber)
- 100% solid state microprocessor-controlled electronics
- Mounting hardware for clamping to posts -- no need for on-site fabrication
- 37-key control console with LCD display
- Junction box and 10 ft. patch cable for data
- Automotive grade baked-on enamel-based paint (choose from 16 standard colors)
- Rust-free aluminum cabinet
- ETL listed to UL standard
- Five-year limited warranty
- Toll-free technical support via phone for the life of the product